



Always be here with you!



CE

WOLF

SKID STEER LOADER



SKID STEER LOADER

USAGE SCENARIOS

Broad vision:

The design of 360°full-view cab remarkably promotes the operation space and thoroughly improves the operation vision.

Modular operation:

Based on the daily operation frequencies of the diversified operation units, the cab is modularly and appropriately arranged to ensure easily accessible operations.

The standard attachment quick change module features rich choice of attachments.

One-stop maintenance:

All filters are arranged at the easily accessible locations to truly realize the one-stop repairs and maintenance without tilting the cab.



Stronger body frame protects operator from danger. The rear window is large and it serves as an emergency exit. Closed cab with broader sight line.

Ergonomically designed safety armrest not only prevents the operator from falling off the chair accidentally, but also can support the operator body to have a rest when he was tired.



Easy Maintenance

The machine's cab can be opened totally with wide turning angle which can save time and improve efficiency in daily maintenance.



Free additional plugs for electronic attachments. The large-flow quick couplings will highlight their advantages in performance when using large-flow attachments.



Imported hydraulic system, superior performance.



All instruments and operating buttons are within the reach of the operator.



There are two extra handles on the outer cabin frame which provide convenience. Ample space also caters to tall machine operators.



Adopts high power engine, more powerful, larger loading capacity.

WHEEL SKID STEER LOADER



Specifications

	ZJ25	ZJ35	ZJ45	ZJ60	ZJ65	ZJ75	ZJ100
Operating load(kg)	300	500	700	850	950	1050	1200
Max Speed(km/h)	9	12	12	12	12	12	12
Rated flux(L/min)	50	60	62.5	75	75	75	88
High flow flux(L/min)	/	/	/	/	125	125	125
Tire(track) model	5.7-12	8.5-15	10-16.5	12-16.5	12-16.5	12-16.5	12-16.5
Rated power(kw)	18.4	29.4	37	45	55	55	75
Fule tank capacity(L)	25	60	70	80	80	75	90
Self weight bucket(kg)	1500	2300	2700	2800	3350	3500	3600
Bucket capacity(m ³)	0.2	0.3	0.4	0.4	0.5	0.5	0.55

Dimension Parameter

	ZJ25	ZJ35	ZJ45	ZJ60	ZJ65	ZJ75	ZJ100
Overall operating height (mm)	3401	3300	3980	4000	4000	4070	4070
Height to bucket hinge pin (mm)	2477	2725	3080	3100	3100	3280	3150
Height to top of cab (mm)	1812	2000	2140	2160	2180	2180	2180
Height to bottom of level bucket(mm)	2446	2558	2913	2933	2962	3140	3140
Without bucket length (mm)	2267	2300	2640	2750	2612	2880	2963
Overall length with bucket(mm)	2768	2950	3420	3490	3392	3580	3735
Dumping angle at maximum height(°)	40	40	40	40	40	40	40
Dumping height(mm)	1990	2050	2380	2400	2400	2500	2500
Dumping reach(mm)	419	790	700	750	750	700	673
Rollback of bucket on ground(°)	30	30	30	30	30	30	30
Rollback of bucket at full height(°)	103	104	104	104	104	104	104
Wheelbase(mm)	801	897	991	991	991	1080	1115
Ground clearance(mm)	145	140	185	205	210	205	205
Angle of departure(°)	20	20	20	20	20	20	20
Front turning radius without bucket(mm)	960	1098	1168	1193	1300	1250	1300
Front turning radius(mm)	1660	1760	1958	1953	2290	2112	2290
Rear turning radius(mm)	1253	1296	1630	1723	1440	1774	1540
Rear axle to bumper (mm)	910	964	1108	1208	1080	1082	1284
Thread width (mm)	785	1080	1450	1500	1500	1500	1500
Width (mm)	880	1350	1720	1880	1680	1880	1880
Bucket width (mm)	915	1400	1740	1880	1730	1880	1880



QINGDAO ZONGJIN ENGINEERING MACHINERY CO.,LTD.

WOLF (QINGDAO) EQUIPMENT CO.,LTD.



Tel: 0086-532-66739792

Email: info@chinawheelloaders.com

WeChat/Whatsapp: +8613589171650

Address: No.88 Chunyang Rd,Chengyang,Qingdao,China